



FOAM PNEUMATIC WHEELS

210-250LBS



FEATURES

BEARINGS: Ball Bearings
TEMPERATURE: -20°F to 130°F
FINISH: Plastic Grey Hub

DESCRIPTION: Foam Pneumatic wheels are excellent for applications where floor and equipment protection is vital. The foam fill provides for shock absorption, quiet operation and ease of rolling. Excellent for delicate materials and uneven and rough floor surfaces. For manual operation only.

EXCELLEN FOR:

- Uneven floors such as agricultural, institutional and industrial
- Shock absorbing uses for indoor and outdoor rough terrain



PNEUMATIC FOAM



PNEUMATIC FOAM GREY

WHEEL

PART NUMBER

Diameter	Tread Width	Capacity Lbs.	Hub Length	Hub Type	Tire Colour	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
6"	2"	210	2 1/2"	Center	Black	1/2"	5/8" * 3/4"	Ball	W-7006-PFCC-BB	0.79
		210	2 1/2"	Center	Grey	1/2"	5/8" * 3/4"	Ball	W-7006-PFCCG-BB	0.79
8"	2 1/2"	235	3"	Center	Black	1/2"	5/8" * 3/4"	Ball	W-7908-PFCE-BB	1.70
		235	3"	Center	Grey	1/2"	5/8" * 3/4"	Ball	W-7908-PFCEG-BB	1.70
10"	3"	250	2 1/4"	Offset	Black	5/8"	-	Ball	W-7910-PFOB	2.10
		250	2 1/4"	Offset	Black	5/8"	1/2" * 3/4"	Ball	W-7910-PFOB-BB	2.51
		250	4"	Center	Black	1/2"	5/8" * 3/4"	Ball	W-7910-PFCF-BB	2.52
		250	4"	Center	Grey	1/2"	5/8" * 3/4"	Ball	W-7910-PFCFG-BB	2.52

HUB SIZE:

HUB LENGTH

CODE#

2"	A
2 1/4"	B
2 1/2"	C
2 5/8"	D
3"	E
3 1/4"	F
4"	F
4 1/4"	H