



7900 SERIES

450 LBS



FEATURES

KINGPIN: 9/16" diameter nut & bolt coined
BALL BEARINGS: 5/16" diameter upper race; 1/4" diameter lower race
BUSHING: Ball bearings
AXLE&NUT: 1/2" axle and lock nut

FINISH: Corrosion resistant bright zinc
HARDENED: Work hardened double ball raceway
SPECIAL: Automotive tire traction; full floor protection; quiet operation
PLY RATING: 4

EXCELLENT FOR:

- Uneven floors such as agricultural, institutional & industrial
- Shock absorbing uses for indoor & outdoor rough terrain



PNEUMATIC



PNEUMATIC GREY



FOAM

WHEEL

CASTER

PART NUMBER

OPTIONS:

- SLB Side Locking Brake


Diameter	Tread Width	Capacity Lbs.	Bearing Type	Swivel Radius	Overall Height	Tire Size	Tire Colour	Leg Spacing	Wheel Type	Swivel	Caster Weight (lbs)	Rigid	Caster Weight (lbs)
8"	2 1/2"	235	Ball	6 1/4"	10"	2.50-4	Black	3"	Foam (HS Sawtooth)	S7908-A38H-PFC-BB	5.60	R7908-A38H-PFC-BB	4.70
		300	Ball	6 1/4"	10"	2.50-4	Black	3"	Pneumatic (Lug)	S7908-A38H-PNC-BB	6.58	R7908-A38H-PNC-BB	5.70
		300	Ball	6 1/4"	10"	2.50-4	Grey	3"	Pneumatic (Lug)	S7908-A38H-PNCG-BB	6.58	R7908-A38H-PNCG-BB	5.70
10"	3"	250	Ball	7 5/8"	12 1/2"	4.10/3.50-4	Black	4"	Foam (HS Sawtooth)	S7910-A38H-PFC-BB	6.90	R7910-A38H-PFC-BB	6.00
		250	Ball	7 5/8"	12 1/2"	4.10/3.50-4	Grey	4"	Foam (HS Sawtooth)	S7910-A38H-PFCG-BB	6.90	R7910-A38H-PFCG-BB	6.00
	3 1/2"	350	Ball	7 5/8"	12 1/2"	4.10/3.50-4	Black	4"	Pneumatic (HS Sawtooth)	S7910-A38H-PNC-BB	7.69	R7910-A38H-PNC-BB	7.32
		350	Ball	7 5/8"	12 1/2"	4.10/3.50-4	Grey	4"	Pneumatic (HS Sawtooth)	S7910-A38H-PNCG-BB	7.69	R7910-A38H-PNCG-BB	7.32
12"	3 1/2"	450	Ball	9"	14"	4.10/3.50-6	Black	4"	Pneumatic (HS Sawtooth)	S7912-A38H-PNC-BB	11.25	R7912-A38H-PNC-BB	10.00
		450	Ball	9"	14"	4.10/3.50-6	Grey	4"	Pneumatic (HS Sawtooth)	S7912-A38H-PNCG-BB	11.25	R7912-A38H-PNCG-BB	10.00

FINISHES:

- 70?A Antique
 70?PB Polished Brass
 70?1 Brass
 70?2 Chrome
 70?4 Black

Inquiries on other finishes welcome

PLATE DIAGRAMS



STANDARD PLATE: A38H

Plate Thickness: 1/4"