

ROLLX™

WHEELS

400-1,800LBS

FEATURES

BEARINGS: Plain, Ball, Delrin, Nylon, Roller, Caged Roller
TEMPERATURE: -45°F to 180°F (with Plastic Side Washer)
 -45°F to 250°F (with Steel Side Washer)
COLOURS: Black
DESCRIPTION: This non-marking wheel features an exclusively developed thermoplastic nylon material which is excellent for high load capacities.

The RollX™ wheel is extremely ergonomically efficient, as it requires minimum effort to roll and swivel with heavy loads. It resists hard impacts and is resistant to most chemicals, solvents, gases, acids, steam cleaning and does not absorb water! This wheel is ideal for industrial and institutional applications.

DUROMETER: 85 (+/-5) D Scale



EXCELLENT FOR:

- Floor protection
- Factory use
- Waste bins
- Platform trucks
- Stock trucks
- Heavy material handling
- Easy rolling
- Heavy loads



ROLLX™



ROLLX™(for WOW)



ROLLX™HEAVY DUTY

OPTIONS:

- BB Ball Bearing
- BR Bronze Bushing
- DB Delrin Bearing
- NB Nylon Roller Bearing
- NBSS Stainless Steel Nylon Roller Bearing
- RB Roller Bearing
- RBC Caged Roller Bearing
- RBSS Stainless Steel Roller Bearing
- SSW Steel Side Washer
- SWH Heat-treated Side Washer
- T Through Bore (2" wheel tread)
- TG Thread Guards

SPECIAL:

- Resistant to most chemicals
- Non-marking
- Moisture Friendly
- Maintenance free
- One piece solid Rollx
- Same capacity as steel wheels
- Easy to assemble

WHEEL						PART NUMBER							
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)					
2 5/8"	1 1/2"	400	1 9/16"	12mm	-	Roller	W-54260-RX-RB-12MM	0.43					
3"	1 1/2"	600	1 5/8"	3/8"	5/16"	Steel	W-6203-RX	0.48					
		600	1 5/8"	1 3/16"	1/2" * 5/8"	Plain	W-6203-RX	0.42					
		600	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6203-RX-RB	0.82					
4"	1 3/8"	600	1 9/16"	1/2"	5/16" * 3/8"	Plain	W-5040-RX	0.66					
		700	1 5/8"	3/8"	5/16"	Steel	W-6204-RX	0.77					
				1 3/16"	1/2" * 5/8"	Plain	W-6204-RX	0.71					
	700	1 1/2"	700	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6204-RX-RB	1.11				
							800	2 3/16"	1 3/16"	-	Plain	W-7004-RX*	0.63
							800	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7004-RX-RB	0.98
5"	1 1/2"	800	1 5/8"	3/8"	5/16"	Steel	W-6205-RX	1.05					
		800	1 5/8"	1 3/16"	1/2" * 5/8"	Plain	W-6205-RX	0.97					
		800	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6205-RX-RB	1.37					
	2"	1,000	1,000	2 3/16"	1 3/16"	-	Plain	W-7005-RX*	0.84				
			1,000	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7005-RX-RB	1.18				
			1,800	2 3/16"	1 3/16"	-	Plain	W-7005-RXHD*	1.16				
			1,800	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7005-RXHD-RB	1.50				
	2 1/2"	1,800	1,800	2 3/4"	1 15/16"	-	Plain	W-7105-RX	1.62				
			1,800	2 27/32"	3/4"	1" * 1 1/4"	Roller	W-7105-RX-RB	3.27				
6"	2"	1,200	2 3/16"	1 3/16"	-	Plain	W-7006-RX*	1.06					
		1,200	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7006-RX-RB	1.40					
		1,800	2 3/16"	1 3/16"	-	Plain	W-7006-RXHD*	1.57					
		1,800	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7006-RXHD-RB	1.98					
	1,600	2 3/16"	1,600	2 3/16"	1 3/16"	-	Plain	W-7006-RXW*	1.64				
			1,600	2 3/8"	1/2"	3/4"	Precision	W-7006-RXW-PB	2.11				
			1,600	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7006-RXW-RB	2.04				
8"	2"	1,400	2 3/16"	1 3/16"	-	Plain	W-7008-RX*	1.84					
		1,400	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7008-RX-RB	2.10					

* wheel has one closed side to eliminate side washer and for easier assembly